

POWER CHOCK® 3

PORTABLE WHEEL RESTRAINT SYSTEM



PROTECT YOUR LOADING DOCK PERSONNEL

POWER CHOCK® 3 is an easy-to-handle, manual wheel restraint system, highly suitable for narrow spaces between loading docks, with an unparalleled quality-price ratio.





EXCLUSIVE



WARRANTY

- RUGGED**
- RELIABLE**
- EASY-TO-HANDLE**



MAINTENANCE-FREE



WINTER RESISTANT



LOWEST TCO



UNIVERSALLY COMPATIBLE



ALL GROUNDS & SPACES



RAPID & INTUITIVE

TECHNICAL SPECIFICATIONS

POWER CHOCK® 3

- ◆ High-tensile steel wheel chock linked to a control box via communication cable installed on a flexible pole.
- ◆ Two sections (totalling 2400 mm) of hot-dip, galvanized steel and ground-fixed restraining plates in the dock bay area. Third section of restraining plate optional.
- ◆ 2 sensors linked to an audiovisual communication system:
 - Equipped with a wheel sensor inside chock to confirm proper wheel chock placement
 - A door sensor to confirm door closure
- ◆ Communication system equipped with an indoor control box, visual indicators (red/green LED lights), and an audible alarm. "Chock engaged" indicator light and self-diagnostic function included. Also equipped with exterior LED traffic lights and audible alarms.
- ◆ A trolley is available as option for easy handling by the driver.

In case of early removal of the chock during loading / unloading, the high-volume alarms and lights - inside and outside of the facility - are activated instantly, in order to allow the loading dock workers to get to safety and to inform the driver that he or she may be responsible for a hazardous situation.



Height	40 cm
Length	54 cm
Width	15 cm
Weight	13 kg

Additional heights and widths available.

DETAILS AND VIDEOS AVAILABLE HERE.

